

Appl. No. 09/656,805
Amdt. Dated July 15, 2005
Reply to Office action of April 15, 2005

Amendments to the Claims:

This listing of claims will replace all prior version, and listings, of claims in the application:

Listing of Claims:

Claims 1-52 (Canceled)

53. (New) A method of manufacturing a hearing device comprising:
manufacturing a first functional part at a first location and of a first material to provide a first function for the hearing device;
manufacturing a second functional part at a second location and of a second material to provide a second function for the hearing device;
assembling said first and second functional parts at a third location to form a composite part to provide both said first and second functions at the hearing device, thereby injection molding said second functional part of said second material integrally with said first part and simultaneously performing manufacturing of said second part of said second material and assembling of said second part and of said first part of said first material, said second location being equal to said third location.

54. (New) The method of claim 53, wherein at least one of the first and second functional parts is a portion of a housing of the hearing device.

55. (New) The method of claim 53, wherein at least one of the first and second functional parts is a seal.

56. (New) The method of claim 53, wherein one of the first and second functional parts is a portion of a housing of the hearing device and the other of the first and second functional parts is a seal.

Appl. No. 09/656,805
Amdt. Dated July 15, 2005
Reply to Office action of April 15, 2005

57. (New) The method of claim 53, wherein at least one of the first and second functional parts is an acoustical conductor.

58. (New) The method of claim 57, wherein the acoustical conductor is formed at an output side of an electromechanical transducer of the hearing device.

59. (New) The method of claim 57, wherein the acoustical conductor is formed at an input side of an acoustical/electrical transducer of the hearing device.

60. (New) The method of claim 53, wherein one of the first and second functional parts is a resilient bush configured to seat a transducer.

61. (New) The method of claim 53 further comprising, forming and joining a third functional part of the hearing device integrally with the first and second functional parts by multi component injection molding.

62. (New) The method of claim 61, wherein the first, second, and third functional parts comprise a housing, a seating bush, and an acoustical conductor.

63. (New) The method of claim 53, wherein said second functional part is a rim portion of a feed-through aperture of a housing.

64. (New) The method of claim 53, wherein the first functional part is a first surface area of a housing for the hearing device and the second functional part is a second surface area of the housing, the second surface area being adjacent to the first surface area.

65. (New) The method of claim 64, wherein the first and second surface areas are differently palpable.

Appl. No. 09/656,805
Amdt. Dated July 15, 2005
Reply to Office action of April 15, 2005

66. (New) The method of claim 53, further comprising mounting a unit of the hearing device into an opening of a bordering area, the bordering area being formed by the first and second functional parts.

67. (New) The method of claim 66, wherein the unit of the hearing device is a manually operable control element.

68. (New) The method of claim 53, wherein said first functional part is injection molded of said first material simultaneously with injection molding said second functional part of said second material, said first, second, and third locations being equal.

69. (New) The method of claim 53, wherein each of the first, second, and third locations are located within a single mold.